



Material	Nickel-plated brass
Seal	NBR
Protection class	IP 54 / IP 65 in case of additional flat seal at connection thread
Temperature range	-20°C to +80°C

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	Item-No
PG 7	6 – 8	5	15	13/14	1.101.0703.01
PG 9	4 – 10	6	15	15/17	1.101.0901.01
PG 9	8 – 10	6	15	15/17	1.101.0903.01
PG 11	6.5 – 12	6	17	18/20	1.101.1101.01
PG 11	10 – 12	6	17	20/18	1.101.1103.01
PG 13.5	6.5 – 13.5	6.5	20	20/22	1.101.1301.01
PG 13.5	12 – 14	6.5	20	20/22	1.101.1303.01
PG 16	6.5 – 16	6.5	22	22/24	1.101.1601.01
PG 16	14 – 16	6.5	22	22/24	1.101.1603.01
PG 21	9 – 20	7	24	28/30	1.101.2101.01
PG 21	17 – 19	7	24	28/30	1.101.2103.01
PG 29	17 – 28	8	26	37/40	1.101.2901.01
PG 29	26 – 28	8	26	37/40	1.101.2903.01
PG 36	23 – 34	9	30	47/50	1.101.3601.01
PG 36	33 – 35	9	30	47/50	1.101.3603.01
PG 42	29 – 40	10	34	54/57	1.101.4201.01
PG 42	39 – 41	10	34	54/57	1.101.4203.01
PG 48	35 – 46	10	37	60/64	1.101.4801.01
PG 48	45 – 47	10	37	60/64	1.101.4803.01