


DIN cable glands

DIN 46320 Z (metric, PG)



Material	Nickel-plated brass
Seal	NBR
Protection class	IP 54 / IP 65 in case of additional flat seal at connection thread
Temperature range	-20°C to +80°C

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	Version	Item-No
M12 x 1.5	6 – 8	5	22	16/14	with sealing ring	1.105.1200.51
M16 x 1.5	6.5 – 10	5	25	19/18	with cut-out sealing ring	1.105.1600.52
M16 x 1.5	8 – 10	5	25	19/18	with sealing ring	1.105.1600.51
M20 x 1.5	7.5 – 12	6	26	22/22	with cut-out sealing ring	1.105.2000.52
M20 x 1.5	8.5 – 13.5	6	27.5	24/22	with cut-out sealing ring	1.105.2013.52
M20 x 1.5	10 – 12	6	26	22/22	with sealing ring	1.105.2000.51
M20 x 1.5	10.5 – 15	6	28.5	26/24	with cut-out sealing ring	1.105.2016.52
M20 x 1.5	12 – 14	6	27.5	24/22	with sealing ring	1.105.2013.51
M20 x 1.5	13 – 15	6	28.5	26/24	with sealing ring	1.105.2016.51
M25 x 1.5	13 – 20	6	33	33/30	with cut-out sealing ring	1.105.2500.52
M25 x 1.5	17 – 19	6	33	33/30	with sealing ring	1.105.2500.51
M32 x 1.5	19 – 28	6	36	42/39	with cut-out sealing ring	1.105.3200.52
M32 x 1.5	26 – 27	6	36	42/39	with sealing ring	1.105.3200.51
M40 x 1.5	24 – 34	7	41	52/50	with cut-out sealing ring	1.105.4000.52
M40 x 1.5	33 – 35	7	41	52/50	with sealing ring	1.105.4000.51
M50 x 1.5	34 – 40	8	45	59/57	with cut-out sealing ring	1.105.5000.52
M50 x 1.5	39 – 41	8	45	59/57	with sealing ring	1.105.5000.51
M63 x 1.5	39 – 46	9	48	64/66	with cut-out sealing ring	1.105.6300.52
M63 x 1.5	43 – 45	9	48	64/66	with sealing ring	1.105.6300.51
PG 7	6 – 8	5	22	16/14	with sealing ring	1.105.0703.01
PG 9	6.5 – 10	6	25	19/17	with cut-out sealing ring	1.105.0901.01
PG 9	8 – 10	6	25	19/17	with sealing ring	1.105.0903.01
PG 11	7.5 – 12	6	26	22/20	with cut-out sealing ring	1.105.1101.01
PG 11	10 – 12	6	26	22/20	with sealing ring	1.105.1103.01
PG 13.5	8.5 – 13.5	6.5	27.5	24/22	with cut-out sealing ring	1.105.1301.01
PG 13.5	12 – 14	6.5	27.5	24/22	with sealing ring	1.105.1303.01
PG 16	10.5 – 16	6.5	28.5	26/24	with cut-out sealing ring	1.105.1601.01
PG 16	14 – 16	6.5	28.5	26/24	with sealing ring	1.105.1603.01
PG 21	13 – 20	7	33	33/30	with cut-out sealing ring	1.105.2101.01
PG 21	17 – 19	7	33	33/30	with sealing ring	1.105.2103.01
PG 29	19 – 28	8	36	42/40	with cut-out sealing ring	1.105.2901.01
PG 29	26 – 28	8	36	42/40	with sealing ring	1.105.2903.01
PG 36	24 – 34	9	41	52/50	with cut-out sealing ring	1.105.3601.01
PG 36	33 – 35	9	41	52/50	with sealing ring	1.105.3603.01
PG 42	34 – 40	10	45	59/57	with cut-out sealing ring	1.105.4201.01
PG 42	39 – 41	10	45	59/57	with sealing ring	1.105.4203.01
PG 48	39 – 46	10	48	64/64	with cut-out sealing ring	1.105.4801.01
PG 48	43 – 45	10	48	64/64	with sealing ring	1.105.4803.01

