


RoHS




Material	INOX 1.4404 / INOX 1.4305
Clamping insert	Polyamide VO according to UL 94
Seal	NBR
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
NEMA type rating	4 / 4X / 6
Temperature range	-40°C to +100°C

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	Ⓢ Nm	Item-No INOX 1.4305	Item-No INOX 1.4404
M12 x 1.5	2 – 5	6.5	19	14/14	4	1.695.1200.51	1.675.1200.51
M12 x 1.5	3 – 6.5	6.5	19	14/14	4	1.695.1200.50	1.675.1200.50
M16 x 1.5	3 – 7	6	22	22/22	5	1.695.1600.51	1.675.1600.51
M16 x 1.5	5 – 10	6	22	22/22	5	1.695.1600.50	1.675.1600.50
M20 x 1.5	7 – 12	6	23	24/24	10	1.695.2000.51	1.675.2000.51
M20 x 1.5	10 – 14	6	23	24/24	10	1.695.2000.50	1.675.2000.50
M25 x 1.5	9 – 16	7	24	30/30	12	1.695.2500.51	1.675.2500.51
M25 x 1.5	13 – 18	7	24	30/30	12	1.695.2500.50	1.675.2500.50
M32 x 1.5	13 – 20	8	31	41/41	15	1.695.3200.51	1.675.3200.51
M32 x 1.5	18 – 25	8	31	41/41	15	1.695.3200.50	1.675.3200.50
M40 x 1.5	20 – 26	8	37	50/50	15	1.695.4000.51	1.675.4000.51
M40 x 1.5	22 – 32	8	37	50/50	15	1.695.4000.50	1.675.4000.50
M50 x 1.5	25 – 31	9	37	60/60	24	1.695.5000.51	1.675.5000.51
M50 x 1.5	32 – 38	9	37	60/60	24	1.695.5000.50	1.675.5000.50
M63 x 1.5	29 – 35	10	38	64/68	30	1.695.6300.51	1.675.6300.51
M63 x 1.5	37 – 44	10	38	64/68	30	1.695.6300.50	1.675.6300.50



Metal cable glands

HSK-INOX (PG, NPT)



Material	INOX 1.4404 / INOX 1.4305
Clamping insert	Polyamide VO according to UL 94
Seal	NBR
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
NEMA type rating	4 / 4X / 6
Temperature range	-40°C to +100°C

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	⊕ Nm	Item-No INOX 1.4404	Item-No INOX 1.4305
PG 7	2 – 5	5	19	14/14	4	1.675.0700.15	1.695.0700.15
PG 7	3 – 6.5	5	19	14/14	4	1.675.0700.01	1.695.0700.01
PG 9	2 – 6	6	21	17/17	6	1.675.0900.15	1.695.0900.15
PG 9	4 – 8	6	21	17/17	6	1.675.0900.01	1.695.0900.01
PG 11	3 – 7	6	22	22/22	5	1.675.1100.15	1.695.1100.15
PG 11	5 – 10	6	22	22/22	5	1.675.1100.01	1.695.1100.01
PG 13.5	5 – 9	6.5	24	22/22	8	1.675.1300.15	1.695.1300.15
PG 13.5	6 – 12	6.5	24	22/22	8	1.675.1300.01	1.695.1300.01
PG 16	7 – 12	6.5	23	24/24	10	1.675.1600.15	1.695.1600.15
PG 16	10 – 14	6.5	23	24/24	10	1.675.1600.01	1.695.1600.01
PG 21	9 – 16	7	24	30/30	12	1.675.2100.15	1.695.2100.15
PG 21	13 – 18	7	24	30/30	12	1.675.2100.01	1.695.2100.01
PG 29	13 – 20	8	29	41/41	15	1.675.2900.15	1.695.2900.15
PG 29	18 – 25	8	29	41/41	15	1.675.2900.01	1.695.2900.01
PG 36	20 – 26	8	35	50/50	15	1.675.3600.15	1.695.3600.15
PG 36	22 – 32	8	35	50/50	15	1.675.3600.01	1.695.3600.01
PG 42	25 – 31	9	37	57/57	24	1.675.4200.15	1.695.4200.15
PG 42	32 – 38	9	37	57/57	24	1.675.4200.01	1.695.4200.01
PG 48	29 – 35	10	38	64/64	30	1.675.4800.15	1.695.4800.15
PG 48	37 – 44	10	38	64/64	30	1.675.4800.01	1.695.4800.01
NPT 3/8"	2 – 6	15	21	17/19	6	1.675.3800.71	1.695.3800.71
NPT 3/8"	4 – 8	15	21	17/19	6	1.675.3800.70	1.695.3800.70
NPT 1/2"	5 – 9	13	24	22/24	8	1.675.1200.71	1.695.1200.71
NPT 1/2"	6 – 12	13	24	22/24	8	1.675.1200.70	1.695.1200.70
NPT 3/4"	9 – 16	13	25	30/30	12	1.675.3400.71	1.695.3400.71
NPT 3/4"	13 – 18	13	25	30/30	12	1.675.3400.70	1.695.3400.70
NPT 1"	13 – 20	19	29	41/41	15	1.675.1000.71	1.695.1000.71
NPT 1"	18 – 25	19	29	41/41	15	1.675.1000.70	1.695.1000.70

