


Plastic cable glands

HSK-K-PVDF (metric, NPT)




Material	PVDF VO according to UL94
Seal	FKM
Protection class	IP 68 – 10 bar / IP 69 K with additional o-ring
NEMA type rating	4 / 4X / 6
Temperature range	-35°C to +150°C
Colour	natural

RoHS

- // With additional premounted O-ring on request
- // Other sealing materials on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	Nm	Item-No
M12 x 1.5	2 – 5	8	21	15/15	1.5	1.299.1200.51
M12 x 1.5	3 – 6.5	8	21	15/15	1.5	1.299.1200.50
M16 x 1.5	2 – 6	8	22	19/19	2	1.299.1600.51
M16 x 1.5	4 – 8	8	22	19/19	2	1.299.1600.50
M20 x 1.5	5 – 9	9	27	24/24	3	1.299.2000.51
M20 x 1.5	6 – 12	9	27	24/24	3	1.299.2000.50
M25 x 1.5	9 – 16	11	31	33/33	4	1.299.2500.51
M25 x 1.5	13 – 18	11	31	33/33	4	1.299.2500.50
M32 x 1.5	13 – 20	11	39	42/42	6	1.299.3200.51
M32 x 1.5	18 – 25	11	39	42/42	6	1.299.3200.50
NPT 3/8"	2 – 6	15	22	19/22	2	1.299.3800.71
NPT 3/8"	4 – 8	15	22	19/22	2	1.299.3800.70
NPT 1/2"	5 – 9	13	27	24/24	3	1.299.1200.71
NPT 1/2"	6 – 12	13	27	24/24	4.5	1.299.1200.70
NPT 1/2"	7 – 12	13	28	27/27	3.5	1.299.1216.71
NPT 1/2"	10 – 14	13	28	27/27	4.5	1.299.1216.70
NPT 3/4"	9 – 16	14	31	33/33	4	1.299.3400.71
NPT 3/4"	13 – 18	14	31	33/33	5	1.299.3400.70






Material	PVDF V0 according to UL94
Seal	FKM
Protection class	IP 68 – 10 bar / IP 69 K with additional o-ring
NEMA type rating	4 / 4X / 6
Temperature range	-35°C to +150°C
Colour	natural

RoHS

- // With additional premounted O-ring on request
- // Other sealing materials on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
PG 7	2 – 5	8	21	15/15	1.5	1.299.0700.15
PG 7	3 – 6.5	8	21	15/15	1.5	1.299.0700.14
PG 9	2 – 6	8	22	19/19	2	1.299.0900.15
PG 9	4 – 8	8	22	19/19	2	1.299.0900.14
PG 11	3 – 7	8	25	22/22	3	1.299.1100.15
PG 11	5 – 10	8	25	22/22	3	1.299.1100.14
PG 13.5	5 – 9	9	27	24/24	3	1.299.1300.15
PG 13.5	6 – 12	9	27	24/24	3	1.299.1300.14
PG 16	7 – 12	10	28	27/27	3.5	1.299.1600.15
PG 16	10 – 14	10	28	27/27	4.5	1.299.1600.14
PG 21	9 – 16	11	31	33/33	4	1.299.2100.15
PG 21	13 – 18	11	31	33/33	4	1.299.2100.14
PG 29	13 – 20	11	39	42/42	6	1.299.2900.15
PG 29	18 – 25	11	39	42/42	6	1.299.2900.14
PG 36	20 – 26	13	48	53/53	9	1.299.3600.15
PG 36	22 – 32	13	48	53/53	10	1.299.3600.14
PG 42	25 – 31	13	49	60/60	11	1.299.4200.15
PG 42	32 – 38	13	49	60/60	15	1.299.4200.14
PG 48	29 – 35	14	49	65/65	10	1.299.4800.15
PG 48	37 – 44	14	49	65/65	18	1.299.4800.14

