

Material	Polyamide V0 according to UL94
Seal	NBR
Protection class	IP 68 – 10 bar / IP 69 K with additional o-ring
NEMA type rating	4 / 4X / 6
Temperature range	-40°C to +100°C
Colour	grey / black
RAL	7035 / 9005

RoHS

// With additional premounted O-ring on request

// Other sealing materials on request


AG	∅k mm	d mm	GL mm	H mm	SW1/SW2 mm	⊕ Nm	Item-No grey	Item-No black
PG 7	2 – 6	7	8	22	19/19	2	1.590.0700.15	1.590.0701.15
PG 7	4 – 8	7	8	22	19/19	2	1.590.0700.14	1.590.0701.14
PG 9	3 – 7	9	8	25	22/22	2.5	1.590.0900.15	1.590.0901.15
PG 9	5 – 10	9	8	25	22/22	3	1.590.0900.14	1.590.0901.14
PG 11	5 – 9	10.5	8	24	24/24	3	1.590.1100.15	1.590.1101.15
PG 11	6 – 12	10.5	8	24	24/24	4.5	1.590.1100.14	1.590.1101.14
PG 13.5	7 – 12	12.5	9	28	27/27	3.5	1.590.1300.15	1.590.1301.15
PG 13.5	10 – 14	12.5	9	28	27/27	4.5	1.590.1300.14	1.590.1301.14
PG 16	9 – 16	15	10	31	33/33	4	1.590.1600.15	1.590.1601.15
PG 16	13 – 18	15	10	31	33/33	5	1.590.1600.14	1.590.1601.14



Plastic cable glands

HSK-KR (PG)

RoHS



Material	Polyamide V0 according to UL94
Seal	NBR
Protection class	IP 68 – 10 bar / IP 69 K with additional o-ring
NEMA type rating	4 / 4X / 6
Temperature range	-40°C to +100°C
Colour	grey / black
RAL	7035 / 9005

// With additional premounted O-ring on request

// Other sealing materials on request



AG	∅k mm	GL mm	H mm	SW1/SW2 mm	⊕ Nm	Item-No grey	Item-No black
PG 9	2 – 5	8	21	15/19	1.5	1.591.0900.15	1.591.0901.15
PG 9	3 – 6.5	8	21	15/19	1.5	1.591.0900.14	1.591.0901.14
PG 11	2 – 6	8	22	19/22	2	1.591.1100.15	1.591.1101.15
PG 11	4 – 8	8	22	19/22	2	1.591.1100.14	1.591.1101.14
PG 13.5	3 – 7	9	25	22/24	2.5	1.591.1300.15	1.591.1301.15
PG 13.5	5 – 10	9	25	22/24	3	1.591.1300.14	1.591.1301.14
PG 16	5 – 9	10	27	24/27	3	1.591.1600.15	1.591.1601.15
PG 16	6 – 12	10	27	24/27	4.5	1.591.1600.14	1.591.1601.14
PG 21	7 – 12	11	28	27/33	3.5	1.591.2100.15	1.591.2101.15
PG 21	10 – 14	11	28	27/33	4.5	1.591.2100.14	1.591.2101.14

