

Material	Nickel-plated brass
Clamping insert	Metallized polyamide
Seal	NBR
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
NEMA type rating	4 / 4X / 6
Temperature range	-40°C to +100°C

RoHS

EMV  
EMC

// Other sealing material e.g. Silicone on request

AG	∅k mm	H mm	SW1/SW2 mm	⊕ Nm	GL mm	Item-No short	GL mm	Item-No long
M12 x 1.5	3 – 6.5	25	14/14	6	6.5	1.631.1200.50	10	1.631.1200.30
M16 x 1.5	4 – 8	29	17/19	9	6	1.631.1609.50	10	1.631.1609.30
M16 x 1.5	5 – 10	32	20/20	11	6	1.631.1600.50	10	1.631.1600.30
M20 x 1.5	6 – 12	32.5	22/22	12	6	1.631.2013.50	10	1.631.2013.30
M20 x 1.5	10 – 14	33	24/24	13	6	1.631.2000.50	10	1.631.2000.30
M25 x 1.5	13 – 18	39	30/30	13	7	1.631.2500.50	12	1.631.2500.30
M32 x 1.5	18 – 25	45	40/40	17.5	8	1.631.3200.50	12	1.631.3200.30
M40 x 1.5	24 – 32	51	50/50	25	8	1.631.4000.50	15	1.631.4000.30
M50 x 1.5	32 – 38	57.5	57/57	29	9	1.631.5000.50	15	1.631.5000.30
M63 x 1.5	37 – 44	52	64/68	34	10	1.631.6300.50	15	1.631.6300.30



to the product video




to the assembly  
instruction



# EMC cable glands

## HSK-M-EMC-D (PG, NPT)



Material	Nickel-plated brass
Clamping insert	Metallized polyamide
Seal	NBR
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
NEMA type rating	4 / 4X / 6
Temperature range	-40°C to +100°C

RoHS

EMV  
EMC

// Other sealing material e.g. Silicone on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No
PG 7	3 – 6.5	5	24	14/14	6	1.631.0700.01
PG 9	4 – 8	6	28	17/17	9	1.631.0900.01
PG 11	5 – 10	6	29	20/20	11	1.631.1100.01
PG 13.5	6 – 12	6.5	31	22/22	12	1.631.1300.01
PG 16	10 – 14	6.5	32	24/24	13	1.631.1600.01
PG 21	13 – 18	7	38	30/30	13	1.631.2100.01
PG 29	18 – 25	8	43	40/40	17.5	1.631.2900.01
PG 36	24 – 32	8	48	50/50	25	1.631.3600.01
PG 42	32 – 38	9	45	57/57	29	1.631.4200.01
PG 48	37 – 44	10	46	64/64	34	1.631.4800.01
NPT 3/8"	4 – 8	15	29	17/19	9	1.631.3800.70
NPT 1/2"	6 – 12	13	32.5	22/24	12	1.631.1200.70
NPT 3/4"	13 – 18	13	39	30/30	13	1.631.3400.70



to the product video



to the assembly  
instruction

