


# Metal cable glands

**HSK-M-Flaka** (metric, PG, NPT)



<b>Material</b>	Nickel-plated brass
<b>Clamping insert</b>	Polyamide V0 according to UL 94
<b>Seal</b>	Elastomer
<b>Material o-ring</b>	NBR
<b>Protection class</b>	IP 65 / IP 68 – 10 bar and optimum assignment of all bores
<b>Temperature range</b>	-40°C to +100°C

RoHS

- // AISI on request
- // Further seal inserts on request
- // Elongated threads on request

AG	GL mm	H mm	SW1/SW2 mm	B x H mm	Item-No	B x H mm	Item-No
M20 x 1.5	6	24	24/24	11.5 x 5	1.688.2016.50	12 x 7	1.688.2017.50
M20 x 1.5	6	24	24/24	14 x 6	1.688.2018.50		
M25 x 1.5	7	26	30/30	14 x 7	1.688.2501.50	14 x 6	1.688.2500.50
M32 x 1.5	8	31	40/40	22 x 8	1.688.3200.50		
M40 x 1.5	8	37	50/50	28.5 x 10	1.688.4000.50	29 x 5.5	1.688.4001.50
M40 x 1.5	8	37	50/50	30.5 x 12	1.688.4002.50	31 x 7.5	1.688.4003.50
M50 x 1.5	9	37	57/57	33.5 x 11.5	1.688.5000.50		
M63 x 1.5	10	38	64/68	38 x 12	1.688.6300.50		
PG 16	6.5	23	24/24	11.5 x 5	1.688.1600.01	12 x 7	1.688.1601.01
PG 16	6.5	23	24/24	14 x 6	1.688.1602.01		
PG 21	7	24	30/30	14 x 7	1.688.2101.01	14 x 6	1.688.2100.01
PG 29	8	29	40/40	22 x 8	1.688.2900.01		
PG 36	8	35	50/50	28.5 x 10	1.688.3600.01	29 x 5.5	1.688.3601.01
PG 36	8	35	50/50	30.5 x 12	1.688.3602.01	31 x 7.5	1.688.3603.01
PG 42	9	37	57/57	33.5 x 11.5	1.688.4200.01		
PG 48	10	38	64/64	38 x 12	1.688.4802.01		
NPT 3/4"	13	25	30/30	14 x 6	1.688.3400.70	14 x 7	1.688.3401.70
NPT 1"	19	29	40/40	22 x 8	1.688.1000.70		

