


EMC cable glands

HSK-MZ-EMC (metric/-long, PG/-long)



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL 94
Seal	NBR
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
NEMA type rating	4 / 4X / 6
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

// *Also available in PVDF on request (-35°C to +150°C)


// Other sealing material e.g. Silicone on request

AG	∅k mm	H mm	SW1/SW2 mm	⊕ Nm	GL mm	Item-No short	GL mm	Item-No long
M12 x 1.5	3 – 6.5	26	14/14	4	6.5	1.692.1200.50	10	1.692.1200.30
M16 x 1.5	5 – 10	29	20/20	5	6	1.692.1600.50	10	1.692.1600.30
M20 x 1.5	10 – 14	32	24/24	10	6	1.692.2000.50	10	1.692.2000.30
M25 x 1.5	13 – 18	35	30/30	12	7	1.692.2500.50	12	1.692.2500.30
M32 x 1.5	18 – 25	41	40/40	15	8	1.692.3200.50	12	1.692.3200.30
M40 x 1.5	22 – 32	48	50/50	15	8	1.692.4000.50	15	1.692.4000.30
M50 x 1.5	25 – 31	51	57/57	24	9	1.692.5000.51	15	1.692.5000.31
M50 x 1.5	32 – 38	51	57/57	24	9	1.692.5000.50	15	1.692.5000.30
M63 x 1.5	29 – 35	52	64/68	30	10	1.692.6300.51	15	1.692.6300.31
M63 x 1.5	37 – 44	52	64/68	30	10	1.692.6300.50	15	1.692.6300.30
PG 7*	3 – 6.5	26	14/14	4	5	1.692.0700.01	10	1.692.0700.60
PG 9*	4 – 8	28	17/17	5	6	1.692.0900.01	10	1.692.0900.60
PG 11*	5 – 10	29	20/20	5	6	1.692.1100.01	10	1.692.1100.60
PG 13.5*	6 – 12	33	22/22	10	6.5	1.692.1300.01	10	1.692.1300.60
PG 16*	10 – 14	32	24/24	10	6.5	1.692.1600.01	10	1.692.1600.60
PG 21*	13 – 18	35	30/30	12	7	1.692.2100.01	12	1.692.2100.60
PG 29*	18 – 25	41	40/40	15	8	1.692.2900.01	12	1.692.2900.60
PG 36*	22 – 32	48	50/50	15	8	1.692.3600.01	15	1.692.3600.60
PG 42*	25 – 31	51	57/57	24	9	1.692.4200.15	15	1.692.4200.61
PG 42*	32 – 38	51	57/57	24	9	1.692.4200.01	15	1.692.4200.60
PG 48*	29 – 35	51	64/64	30	10	1.692.4800.15	15	1.692.4800.61
PG 48*	37 – 44	51	64/64	30	10	1.692.4800.01	15	1.692.4800.60



to the product video






Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL 94
Seal	NBR
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
NEMA type rating	4 / 4X / 6
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

// Other sealing material e.g. Silicone on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
NPT 3/8"	4 – 8	15	28	17/19	5	1.692.3800.70
NPT 1/2"	6 – 12	13	29	22/24	10	1.692.1200.70
NPT 3/4"	13 – 18	13	35	30/30	12	1.692.3400.70



to the product video

