


Metal cable glands


HSK-MZ-PVDF (metric, PG, NPT)



Material	Nickel-plated brass
Clamping insert	PVDF
Seal	FKM
Material o-ring	FKM
Protection class	IP 68 – 10 bar / IP 69 K
Temperature range	-35°C to +150°C

RoHS

// Other sealing material e.g. Silicone on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1.5	3 – 6.5	6.5	26	14/14	4	1.669.1200.50
M16 x 1.5	4 – 8	6	28	19/19	6	1.669.1600.50
M16 x 1.5	5 – 10	6	30	20/20	5	1.669.1611.50
M20 x 1.5	6 – 12	6	33	22/22	8	1.669.2000.50
M20 x 1.5	10 – 14	6	33	24/24	10	1.669.2016.50
M25 x 1.5	13 – 18	7	37	30/30	12	1.669.2500.50
M32 x 1.5	18 – 25	8	43	40/40	15	1.669.3200.50
M40 x 1.5	22 – 32	8	50	50/50	15	1.669.4000.50
PG 7	3 – 6.5	5	26	14/14	4	1.669.0700.01
PG 9	4 – 8	6	28	17/17	6	1.669.0900.01
PG 11	5 – 10	6	30	20/20	5	1.669.1100.01
PG 13.5	6 – 12	6.5	33	22/22	8	1.669.1300.01
PG 16	10 – 14	6.5	33	24/24	10	1.669.1600.01
PG 21	13 – 18	7	37	30/30	12	1.669.2100.01
PG 29	18 – 25	8	43	40/40	15	1.669.2900.01
PG 36	22 – 32	8	50	50/50	15	1.669.3600.01
PG 42	25 – 31	9	51	57/57	24	1.669.4200.15
PG 42	32 – 38	9	51	57/57	24	1.669.4200.01
PG 48	29 – 35	10	51	64/64	30	1.669.4800.15
PG 48	37 – 44	10	52	64/64	30	1.669.4800.01
NPT 3/8"	4 – 8	15	28	17/19	6	1.669.3800.70
NPT 1/2"	7 – 12	13	33	22/24	8	1.669.1200.70
NPT 3/4"	13 – 18	13	37	30/30	12	1.669.3400.70

