

Material	Nickel-plated brass
Seal	TPE
Material o-ring	NBR
Protection class	IP 68
Temperature range	-20°C to +100°C

RoHS


// Other thread pitches on request
 // AISI on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	⊕ Nm	Item-No
M6 x 1	2 – 3.2	6	10	8/8	1	1.106.0601.50
M8 x 0.75	2 – 4.5	3.5	14.3	11/11	2	1.112.0801.01
M8 x 1.25	3 – 5	6	13	11/11	2	1.106.0801.50
M8 x 1.25	3 – 5	10	13	11/11	2	1.106.0801.30
M10 x 1.5	4 – 6	6	14	12/12	1	1.106.1001.50
M10 x 1.5	4 – 6	10	14	12/12	1	1.106.1001.30
PG 7	2 – 4.5	3.5	14.3	11/15	2	1.112.0708.01



Metal cable glands

HSK-Mini (metric/-long)



Material	Nickel-plated brass
Seal	FKM
Material o-ring	FKM
Protection class	IP 68
Temperature range	-25°C to +200°C

RoHS

- // Other thread pitches on request
- // AISI on request

AG	∅k mm	H mm	SW1/SW2 mm	⌚ Nm	GL mm	Item-No short	GL mm	Item-No long
M6 x 1	2 – 3.2	10	8/8	1	6	1.106.0600.55		
M8 x 1.25	3 – 5	13	11/11	2	6	1.106.0800.55	10	1.106.0800.35
M10 x 1.5	4 – 6	14	12/12	1	6	1.106.1000.55	10	1.106.1000.35

