


Plastic cable glands

HSK-W (metric, PG, NPT)



| | |
|-------------------|-----------------|
| Material | Polyamide |
| Seal | NBR |
| Material o-ring | NBR |
| Protection class | IP 68 |
| Temperature range | -40°C to +100°C |
| Colour | black / grey |
| RAL | 9005 / 7035 |

RoHS

// Other sealing material e.g. Silicone on request

| AG | ∅k mm | GL mm | H mm | L mm | SW mm | ⊕ Nm | Item-No grey | Item-No black |
|-----------|----------|----------|---------|---------|----------|---------|-----------------|------------------|
| M16 x 1.5 | 2-6 | 8 | 23 | 45 | 19 | 2.5 | 1.313.1600.51 | 1.313.1601.51 |
| M16 x 1.5 | 4-8 | 8 | 23 | 45 | 19 | 2.5 | 1.313.1600.50 | 1.313.1601.50 |
| M20 x 1.5 | 5-9 | 9 | 30.5 | 57 | 24 | 4 | 1.313.2000.51 | 1.313.2001.51 |
| M20 x 1.5 | 6-12 | 9 | 30.5 | 57 | 24 | 4 | 1.313.2000.50 | 1.313.2001.50 |
| M25 x 1.5 | 9-16 | 11 | 40 | 73 | 33 | 6 | 1.313.2500.51 | 1.313.2501.51 |
| M25 x 1.5 | 13-18 | 11 | 40 | 73 | 33 | 6 | 1.313.2500.50 | 1.313.2501.50 |
| M32 x 1.5 | 13-20 | 11 | 51.5 | 91 | 42 | 9 | 1.313.3200.51 | 1.313.3201.51 |
| M32 x 1.5 | 18-25 | 11 | 51.5 | 91 | 42 | 9 | 1.313.3200.50 | 1.313.3201.50 |
| PG 9 | 2-6 | 8 | 23 | 45 | 19 | 2.5 | 1.313.0900.15 | 1.313.0901.15 |
| PG 9 | 4-8 | 8 | 23 | 45 | 19 | 2.5 | 1.313.0900.14 | 1.313.0901.14 |
| PG 11 | 3-7 | 8 | 27 | 50 | 22 | 2.5 | 1.313.1100.15 | 1.313.1101.15 |
| PG 11 | 5-10 | 8 | 27 | 50 | 22 | 4 | 1.313.1100.14 | 1.313.1101.14 |
| PG 13.5 | 5-9 | 9 | 30.5 | 57 | 24 | 4 | 1.313.1300.15 | 1.313.1301.15 |
| PG 13.5 | 6-12 | 9 | 30.5 | 57 | 24 | 4 | 1.313.1300.14 | 1.313.1301.14 |
| PG 16 | 7-12 | 10 | 32.5 | 59 | 27 | 4 | 1.313.1600.15 | 1.313.1601.15 |
| PG 16 | 10-14 | 10 | 32.5 | 59 | 27 | 6 | 1.313.1600.14 | 1.313.1601.14 |
| PG 21 | 9-16 | 11 | 40 | 73 | 33 | 6 | 1.313.2100.15 | 1.313.2101.15 |
| PG 21 | 13-18 | 11 | 40 | 73 | 33 | 6 | 1.313.2100.14 | 1.313.2101.14 |
| PG 29 | 13-20 | 11 | 51.5 | 91 | 42 | 9 | 1.313.2900.15 | 1.313.2901.15 |
| PG 29 | 18-25 | 11 | 51.5 | 91 | 42 | 9 | 1.313.2900.14 | 1.313.2901.14 |
| NPT 3/8" | 2-6 | 15 | 23 | 45 | 19 | 2.5 | 1.313.3800.71 | 1.313.3801.71 |
| NPT 3/8" | 4-8 | 15 | 23 | 45 | 19 | 2.5 | 1.313.3800.70 | 1.313.3801.70 |
| NPT 1/2" | 5-9 | 13 | 32.5 | 57 | 24 | 4 | 1.313.1200.71 | 1.313.1201.71 |
| NPT 1/2" | 6-12 | 13 | 32.5 | 57 | 24 | 4 | 1.313.1200.70 | 1.313.1201.70 |
| NPT 1/2" | 7-12 | 13 | 32.5 | 59 | 27 | 4 | 1.313.1216.71 | 1.313.1217.71 |
| NPT 1/2" | 10-14 | 13 | 32.5 | 59 | 27 | 6 | 1.313.1216.70 | 1.313.1217.70 |
| NPT 3/4" | 9-16 | 13 | 40 | 73 | 33 | 6 | 1.313.3400.71 | 1.313.3401.71 |
| NPT 3/4" | 13-18 | 13 | 40 | 73 | 33 | 6 | 1.313.3400.70 | 1.313.3401.70 |
| NPT 1" | 13-20 | 19 | 51.5 | 91 | 42 | 9 | 1.313.1000.71 | 1.313.1001.71 |
| NPT 1" | 18-25 | 19 | 51.5 | 91 | 42 | 9 | 1.313.1000.70 | 1.313.1001.70 |

