



Material	Polyamide
Seal	NBR
Material o-ring	NBR
Protection class	IP 68
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

RoHS

- // Other sealing material e.g. Silicone on request
- // Version rotatable

AG	∅k mm	GL mm	H mm	L mm	SW mm	⊕ Nm	Item-No grey	Item-No black
PG 9	2 – 6	8	28	45	19	2.5	1.317.0900.15	1.317.0901.15
PG 9	4 – 8	8	28	45	19	2.5	1.317.0900.14	1.317.0901.14
PG 11	3 – 7	8	32	50	22	2.5	1.317.1100.15	1.317.1101.15
PG 11	5 – 10	8	32	50	22	4	1.317.1100.14	1.317.1101.14
PG 13.5	5 – 9	9	35.5	57	24	4	1.317.1300.15	1.317.1301.15
PG 13.5	6 – 12	9	35.5	57	24	4	1.317.1300.14	1.317.1301.14
PG 16	7 – 12	11	46	73	33	4	1.317.1600.15	1.317.1601.15
PG 16	10 – 14	10	38.5	59	27	6	1.317.1600.14	1.317.1601.14
PG 21	9 – 16	11	46	73	33	6	1.317.2100.15	1.317.2101.15
PG 21	13 – 18	11	46	73	33	6	1.317.2100.14	1.317.2101.14

