


|                   |                     |
|-------------------|---------------------|
| Material          | Nickel-plated brass |
| Clamping insert   | Polyamide           |
| Seal              | NBR                 |
| Material o-ring   | NBR                 |
| Protection class  | IP 68 – 5 bar       |
| Temperature range | -40°C to +100°C     |

RoHS

EMV  
EMC

| AG        | ∅k<br>mm | GL<br>mm | H<br>mm | SW1/SW2<br>mm | <br>Nm | Item-No       |
|-----------|----------|----------|---------|---------------|---|---------------|
| M12 x 1.5 | 3 – 6.5  | 6        | 19.4    | 14/14         | 3   | 1.607.1200.50 |
| M16 x 1.5 | 4.5 – 10 | 6        | 24.4    | 19/19         | 6.5   | 1.607.1600.50 |
| M20 x 1.5 | 6 – 12   | 6        | 25.4    | 22/22         | 6   | 1.607.2013.50 |
| M20 x 1.5 | 7.5 – 14 | 6        | 28.3    | 24/24         | 8   | 1.607.2000.50 |
| M25 x 1.5 | 9 – 17   | 7        | 29.3    | 29/29         | 9.5   | 1.607.2500.50 |
| M32 x 1.5 | 11 – 21  | 8        | 37.7    | 34/34         | 13.5  | 1.607.3200.50 |
| M40 x 1.5 | 19 – 28  | 8        | 40.7    | 44/44         | 32  | 1.607.4000.50 |
| M50 x 1.5 | 27 – 35  | 9        | 50.7    | 55/55         | 40  | 1.607.5000.50 |
| M63 x 1.5 | 34 – 48  | 10       | 55.7    | 68/68         | 46  | 1.607.6300.50 |



to the product video



to the assembly  
instruction

