


Material	Nickel-plated brass
Seal	FKM
Material o-ring	FKM
Protection class	IP 68
Temperature range	-25°C to +200°C

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1.5	4 – 6	5	18	14/14	4	1.106.1200.58
M16 x 1.5	7 – 9	5	19	18/18	6	1.106.1600.58
M20 x 1.5	10 – 13	6	21	22/22	8	1.106.2000.58
M25 x 1.5	15 – 18	7	23	28/28	12	1.106.2500.58
M32 x 1.5	20 – 24	8	26	35/35	15	1.106.3200.58
M40 x 1.5	27 – 32	8	27	45/45	15	1.106.4000.58
M50 x 1.5	35 – 40	10	28	55/55	24	1.106.5000.58
M63 x 1.5	45 – 52	10	36	68/68	30	1.106.6300.58
PG 7	5 – 7	6	16	14/14	4	1.106.0700.80
PG 9	6 – 8	6	17	18/18	6	1.106.0900.80
PG 9	7 – 10	6	17	18/18	6	1.106.0901.80
PG 11	6 – 8	6	20	18/18	6	1.106.1100.80
PG 11	8 – 12	6	20	18/18	6	1.106.1102.80
PG 13.5	11 – 15	6	21	24/24	8	1.106.1300.80
PG 16	11 – 15	6	21	24/24	10	1.106.1600.80
PG 21	15 – 20.5	7.5	22.5	32/32	12	1.106.2100.80
PG 29	20 – 27	8	24	40/40	15	1.106.2900.80